

PosiTest[®] *Accurate & Dependable*

For the non-destructive measurement of non-magnetic coatings (paint, enamel, galvanizing, metalizing, plating, etc.) on STEEL



Stable design with additional
tail-end support. No annoying
rocking during measurement.

DeFelsko[®]
The Measure of Quality

PosiTest[®] *Accurate & Dependable*

***For the non-destructive measurement of non-magnetic coatings
(paint, enamel, galvanizing, metalizing, plating, etc.) on STEEL***

ACCURATE

- Certificate of Calibration showing traceability to NIST included with every gage
- Matching Calibration Standards and Procedures available for every model
- Highly wear resistant Carbide Probe for longest life and continuous accuracy
- Removable center of dial cover for easy calibration adjustment
- Conforms to national and international standards

DURABLE

- Extra rugged housing, not affected by mechanical shock, water, acid or solvents
- Unique overall design, fully supported, positive positioning, no pivoting tendencies during measurement
- Can be used fully supported or with only the front probe area contacting the surface
- Functions on a permanent rare-earth cobalt magnet
- No batteries/electronics
- 2 year warranty

EASY TO USE

- Positive visual and audible indicators to designate when thickness reading is established
- "V" grooves in probe housing and Gage base allow correct positioning on cylindrical objects
- Compact, lightweight, precisely balanced, independent of gravity – can be used in any position
- GO/NO-GO button can be pre-set for rapid measurement
- Probe contact and dial rotation all in a one-finger operation
- Furnished with wrist strap and instructions in a high quality leather case with belt loops for your convenience



Carbide measuring probe for long life.

***FOR: Hot dip galvanizing, hard chrome metalizing,
paint, enamel coatings on steel***



Scale FM 0 – 80 mils
Tolerance: ±0.2 mils up to 4 mils
±5% of the reading over 4 mils

Scale F 0 – 2000 microns
Tolerance: ±5 microns up to 100 microns
±5% of the reading over 100 microns

***FOR: Electroplating, thin paint films,
phosphating on steel***



Scale GM 0 – 8 mils
Tolerance: ±0.04 mils up to 0.8 mils
±5% of the reading over 0.8 mils

Scale G 0 – 200 microns
Tolerance: ±1 micron up to 20 microns
±5% of the reading over 20 microns

DeFelsko[®]
The Measure of Quality

DeFelsko Corporation • 800 Proctor Ave., Ogdensburg, New York 13669-2205 USA
Toll Free 1-800-448-3835 • Tel: +1-315-393-4450 • Fax: +1-315-393-8471
Web: www.defelsko.com • E-mail: techsale@defelsko.com

