

## SAMPLE CERTIFIED TEST DISKS

## Traceability:

The Impressor test disks supplied with this order have been tested using a Vickers hardness tester, serial number 210650A. The Vickers hardness tester has been certified using test blocks that have been calibrated on a verified Laboratory Standard Tester using measuring devices traceable to the National Institute of Standards and Technology. An average of five tests produced results within the tolerance allowed by ASTM Standard E-384.

## VICKERS TEST C 13-Dec-18

Each disk has been tested five times. All five Vickers readings and the average valle are listed below. Each disk marked with an identifying number. Please keep a copy of this votermant with each test disk in use. Permission is granted to copy and distribute as required. A copy is kept on file in electronic format.

## Impressor Test Disk Log Sheet

Part Number	F cory Order Number
GYZ -250-100 Tripe was steemadel	SAP# 1555835 (14)
AM	ESIDLE
Vickers Tester	
Load S Kg	LESM
8 3 F 10	10

ייס	Vickers	Tester		
	Load	C Kg		

Test	Disk #1	Dick t.2	Disk #3	Disk #4	Dis 15
1	139.0	5 44.0	144.0	187.0	137.0
2	144.6	144.0	138.0	142.0	144.0
SIN	138.0	144.0	1300	138.0	143.0
4	140.0	138.0	144.0	142.0	144,0
5	Mah	140.0	143.0	141.0	144.0

Average Vickers Hardness	140.8	142.0	141.6	140.0	142.4
Equivalent GYZ)- 934-1 Value	89	89	89	88	89

InstruCon #:



Order #:

Model: GYZJ-934-1

Humidity:

% R.H. Range 40 - 80%





Serial Number:

St	andards and	Technology (N	IST) and using InstruC	on Inc. or Original Ed	quipment N	Manufacture Vo	k Instructions that
CO	mply with th	e following stan	dard: ISO 10012-1. A.	av er, ge or five test pr	oduced res	ults with p the to	lerance allowed by
A	STM Standar	d E-384.				2	
7	est Equipm	ent	C MIA.		7/10		
Г	/anufacture		Serial# Los	ad Test Dite		Recall Dat	te
	ickers	101	250128 5 K			13-Jul-19	
_			230120 34	10-041-10		13-541-	
J	Results	// · ·		(8)		10	
•	Test Lisk Pa	rt Number GY	ZJ-250-100; Factory C	order Number SAP# 1	52457( (1)	): Te t Disk#1	
					. 1	11.	
		6			5		
		Vickers	Impressor	Impressor Liter		Minimum	Maximu
	Test	Reading*	Before Repair/Cal	Rep. ir/C.2	Delta	Reading	R ea ding
	1	138.0	88	88	N/A	87	89
	2	138.0	Ce	88	N/A	CY	89
T.	3	138.0	88	88	N. A	87	89
8	4	130.0	88	88	MA	87	89
	5	135.0	88	88	N/A	87	89
,	Vote: * Vic	kers Average	Reading of 136.0 i	s Equivalent to GY	ZJ-934-1	Reading of 8	8.
•	1010.	onoro rivorage	recurring of 15 har	o 2 di 2 i montre de 2 i		210111111111111111111111111111111111111	
		9	ーハワレ		** -		
	As I	ound Condition		ce			
	120		Y In Tolerance				
	A	s Left Condition	200				
	12	Calibration Date	X In Tolerance :: 08/07/2018				
	1	Recall Date		Technic	ian·		

InstruCon, Inc. certifies that the Barcol Impressor Hand Held Hardness Tester above was repaired, tested and calil rated. Comparison reading was obtained using a Vickers hardness tester, which has been certified using test blocks in it have been calibrated and verified to Laboratory Standard Tester using measuring devices traceable to the National Institute of